



Plant Hire Sales & Repair

Ardoch Farm, Old Glasgow Road, Kilwinning, North Ayrshire, KA13 7QJ Tel: 01294 557835


Email: info@kattrak.com

Bergmann Dumper 3012 R swivel tip



Main Features:

- High stability thanks to oscillating axle
- Swivelling operator's stand
- ► Electro hydraulic spring type cylinder park brake
- Compact dimensions with low weight





Bergmann Dumper 3012 swivel tip

Technical Data

Weight / Bucket capacity	Payload	12.000 kg
	Unladen weight	11.600 kg
	Bucket capacity struck	6,3 m ³
	Bucket capacity heaped	8,0 m ³
	Bucket system	Hydraulical swivel tip
	,	, .
Dimensions	Height with cabine	3.000 mm
	Total length	6.930 mm
	Total width	2.500 mm
	Ground clearance	430 mm
Transmission	on Load-depending shift – manually shiftably by hand and automatically, self-adjusting optimisation of traction force and speed, speed control stepless	
	forward and backwards, ZF-Ergo-Power transmission	
	1. gear F - 5 km/h 2. Ga	ing2. gear F - 9 km/h
	3. gear F - 14 km/h	4. gear F - 21 km/h
	5. gear F - 32 km/h	6. gear F - 40 km/h
	1. gear R - 6 km/h	2. gear R - 14 km/h
	3. gear R - 34 km/h	
Steering	Hydraulical articulated steering actir	ng over priority valve
	articulation: 37° left & right	
Axles / brakes	Suspended front axle, rear axle fix, maintenance-free-oil-bath multi-disc	
	brake in the wheel hubs with self-locking differential with a locking value of 45 %, hydraulically applicated spring-type cylinder locking brake acting	
	over articulated shaft on front and re	ear axle.
	4 1: 1 6 . 6: 1 .	
Engine	4-cylinder Cummins Diesel engine –	
	power 119 KW with 2.200 rpm - TIER	4 interim
-	Ct.	
Tyres	Standard 20.5 R 25 double coin	
Danmat	Faculty and a state of the stat	amilia painte thanke to wide an anima
Bonnet		service points thanks to wide opening
	sectioned bonnet	
Tank capacity	Fuel 190 L	
Talik Capacity	Hydraulic oil 80 L	
	Trydraulic oli 80 E	
Electrics	24 V electric system with main switcl	h fault finding modus fuel and hour
	counter, control lamps for engine oil	_
	•	draulic filter, display for drive position
	and the state of t	and the first in any for any control
Standard equipment	Comfortable driver's cab with air-sus	spended driver's seat, swivelling
a-a-darkmana		cording to German traffic regulations,
	hardox plates in the bucket, flashing yellow light, cigarette lighter, roller	
	blind for front windscreen, device fo	
	EC declaration of conformity	
	2.2.2.2.2.2.2.2.2.2.2.2.2.2.2.2.2.2.2.2.	